



SINGLE DUCTLESS SPLIT SYSTEMS



Optional accessories available. Visit www.mrslim.ca for more information.



HEAT PUMP VCSi

- Catechin Plus Air Purifying System
- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings (up to 30%)
- Auto Change Over Between Cooling & Heating
- Super-Quiet Technology - Only 19dB(A)
- High-Speed Cooling and Heating
- Wide Airflow - Up to 150"
- Long Pipe Runs - Up to 100 ft.
- Low-Ambient Heating -20°C/-4°F (MSZ-GE models)
- Refrigerant Pre-Charged
- Easy Installation - No Ductwork Needed
- Optional Wired Remote Controller
- 5-Year Parts Warranty
- 7-Year Compressor Warranty

| Model (Heat Pump) | | | MSZ-GE09NA ★ | MSZ-GE12NA ★ | MSZ-GE15NA ★ | MSZ-GE18NA | MSZ-GE24NA ★ | MSZ-D30NA | MSZ-D36NA |
|------------------------------|----------------|-------|--|--|--|--|---|--|----------------------------------|
| Capacity (Rated) | Cooling | Btu/h | 9,000 | 12,000 | 14,000 | 17,200 | 22,500 | 30,700 | 33,200 |
| Capacity (Min. ~ Max.) | | Btu/h | 3,800 ~ 12,200 | 3,800 ~ 13,600 | 3,100 ~ 18,200 | 3,700 ~ 18,700 | 8,200 ~ 31,400 | 9,800 ~ 30,700 | 9,800 ~ 33,200 |
| Capacity (Rated) | Heating @ 47°F | Btu/h | 10,900 | 14,400 | 18,000 | 21,600 | 27,600 | 32,600 | 35,200 |
| Capacity (Max.) | | Btu/h | 4,500 ~ 14,100 | 5,500 ~ 18,100 | 4,800 ~ 20,900 | 3,500 ~ 25,200 | 7,500 ~ 36,900 | 8,700 ~ 34,000 | 8,700 ~ 36,000 |
| Capacity (Rated) | Heating @ 17°F | Btu/h | 6,600 | 8,800 | 11,300 | 13,400 | 16,000 | 19,500 | 21,800 |
| Capacity (Max.) | | Btu/h | 8,700 | 11,200 | 15,900 | 17,200 | 24,600 | 20,800 | 22,800 |
| Power Consumption | Cooling | W | 660 (205 ~ 1,200) | 960 (205 ~ 1,300) | 1,080 (160 ~ 2,000) | 1,640 (240 ~ 2,070) | 1,800 (570 ~ 3,580) | 3,850 (620 ~ 3,850) | 4,360 (620 ~ 4,360) |
| Rated (Min. ~ Max.) | Heating @ 47°F | W | 760 (255 ~ 1,200) | 1,170 (340 ~ 1,660) | 1,600 (270 ~ 2,010) | 1,900 (230 ~ 2,680) | 2,340 (520 ~ 3,650) | 3,360 (520 ~ 3,600) | 3,840 (520 ~ 4,100) |
| Rated (Max.) | Heating @ 17°F | W | 700 (950) | 900 (1,200) | 1,150 (1,950) | 1,450 (2,080) | 1,770 (3,290) | 2,620 | 3,000 |
| EER | Cooling | | 13.6 | 12.5 | 13.0 | 10.5 | 12.5 | 8.0 | 7.6 |
| SEER | Cooling | | 21.0 | 20.5 | 21.0 | 19.2 | 19.0 | 14.5 | 14.5 |
| HSPF (IV) | Heating | | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 8.2 | 8.2 |
| Capacity Control | | | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) | Variable Speed Compressor (VCSi) |
| Refrigerant | | | R-410A | R-410A | R-410A | R-410A | R-410A | R-410A | R-410A |
| Power Supply | V, Phase, Hz | | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 |
| Moisture Removal | Pints/h | | 1.5 | 2.5 | 2.7 | 4.6 | 5.1 | 9.9 | 11.3 |
| Airflow (Q,L,M,H,SH) | CFM Dry | | 145-170-237-321-399 | 145-170-237-321-399 | 205-272-335-420-533 | 230-275-339-420-533 | N/A-388-469-628-738 | N/A-389-639-848-887 | N/A-389-639-848-887 |
| Sound Indoor (Q,L,M,H,SH) | Cooling | dB(A) | 19-22-30-37-43 | 19-22-30-37-45 | 26-32-38-44-49 | 28-33-38-44-49 | N/A-34-41-49-53 | N/A-32-42-49-51 | N/A-32-42-49-51 |
| Sound Outdoor | Cooling | dB(A) | 46 | 49 | 49 | 54 | 55 | 55 | 56 |
| Max. Fuse Size | Indoor | A | 15 | 15 | 15 | 15 | 20 | 15 | 15 |
| (Time Delay) | Outdoor | A | 15 | 15 | 15 | 15 | 20 | 25 | 25 |
| Min. Ampacity | Indoor | A | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| | Outdoor | A | 12 | 12 | 12 | 14 | 17.1 | 21 | 21 |
| Fan Speed Control | | | 6 (Auto, SuperHi, Hi, Med, Low, Quiet) | 6 (Auto, SuperHi, Hi, Med, Low, Quiet) | 6 (Auto, SuperHi, Hi, Med, Low, Quiet) | 6 (Auto, SuperHi, Hi, Med, Low, Quiet) | 5 (Auto, Powerful, Hi, Med, Low) | 5 (Auto, Powerful, Hi, Med, Low) | 5 (Auto, Powerful, Hi, Med, Low) |
| Horizontal Airflow Direction | | | Manual | Manual | Manual | Manual | Manual, Swing | Manual, Swing | Manual, Swing |
| Vertical Airflow Direction | | | Auto, Manual, Swing | Auto, Manual, Swing | Auto, Manual, Swing | Auto, Manual, Swing | Auto, Manual, Swing | Auto, Manual, Swing | Auto, Manual, Swing |
| Air Filters (Washable) | | | Catechin Plus Air Purifying System (Catechin Plus Pre-Filter, Anti-allergy Blue Enzyme Filter) | | | | Platinum Filter, Blue Enzyme Filter | Catechin Plus Air Purifying System (Catechin Plus Pre-Filter, Anti-allergy Blue Enzyme Filter) | |
| Dimension | Indoor | in. | 11-5/8 x 31-7/16 x 9-1/8 | 11-5/8 x 31-7/16 x 9-1/8 | 11-5/8 x 31-7/16 x 9-1/8 | 11-5/8 x 31-7/16 x 9-1/8 | 12-13/16 x 43-5/16 x 9-3/8 | 14-3/8 x 46-1/16 x 11-5/8 | 14-3/8 x 46-1/16 x 11-5/8 |
| (H x W x D) | Outdoor | in. | 21-5/8 x 31-1/2 x 11-1/4 | 21-5/8 x 31-1/2 x 11-1/4 | 21-5/8 x 31-1/2 x 11-1/4 | 33-7/16 x 33-1/16 x 13 | 34-5/8 x 33-1/16 x 13 | 33-7/16 x 33-1/16 x 13 | 33-7/16 x 33-1/16 x 13 |
| Weight | Indoor | lbs. | 22 | 22 | 22 | 22 | 37 | 40 | 40 |
| | Outdoor | lbs. | 66 | 77 | 80 | 119 | 119 | 141 | 141 |
| Pipe Size | Liq. X Gas | in. | 1/4 x 3/8 | 1/4 x 3/8 | 1/4 x 1/2 | 1/4 x 1/2 | 3/8 x 5/8 | 3/8 x 5/8 | 3/8 x 5/8 |
| Max. Height Difference | | ft. | 40 | 40 | 40 | 50 | 50 | 50 | 50 |
| Max. Pipe Length | | ft. | 65 | 65 | 65 | 100 | 100 | 100 | 100 |
| Outdoor Operating Range | Cooling | | 14 - 115°FDB | 14 - 115°FDB | 14 - 115°FDB | 14 - 115°FDB | 14 - 115°FDB | 14 - 115°FDB | 14 - 115°FDB |
| | Heating | | -4 - 75°FDB (-5 - 65°FWB) | -4 - 75°FDB (-5 - 65°FWB) | -4 - 75°FDB (-5 - 65°FWB) | -4 - 75°FDB (-5 - 65°FWB) | -4 - 75°FDB (-5 - 65°FWB) | 14 - 75°FDB (13 - 65°FDB) | 14 - 75°FDB (13 - 65°FDB) |
| Features | | | Econo Cool • Quiet Mode • Smart Set • Super Hi Fan Speed • Low Ambient Heating | | | | Econo Cool • Powerful Mode • Wide Airflow | | |

Q=Quiet, L=Low, M=Med, H=Hi, SH=SuperHi
 All features may not apply to all models. Ask your dealer for details.
 ★ THIS SYMBOL DENOTES AN ENERGY STAR-CERTIFIED UNIT

All test conditions are based on ARI 210/240.
 Rating conditions: Cooling - Indoor: 80°FDB, 67°FWB; Outdoor: 95°FDB, 75°FWB; Rated frequency
 Heating - Indoor: 70°FDB, 60°FWB; Outdoor: 47°FDB, 43°FWB; Rated frequency

